



CAD5

P70/P5 DIP SWITCHES SETTING : 1(Pulse/ICT)

Supported bill Can\$ 5, 10, 20, 50, 100 5bills.

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW9	SW10
★ 1 Pulse / Can\$ 5	OFF	OFF	OFF							
2 Pulse / Can\$ 5	OFF	OFF	ON							
3 Pulse / Can\$ 5	OFF	ON	OFF							
4 Pulse / Can\$ 5	OFF	ON	ON							
5 Pulse / Can\$ 5	ON	OFF	OFF							
10 Pulse / Can\$ 5	ON	OFF	ON							
20 Pulse / Can\$ 5	ON	ON	OFF							
100 Pulse / Can\$ 5	ON	ON	ON							
Fast output Pulse <small>Lo= 50ms Hi=100ms</small>				ON						
★ Slow output Pulse <small>Lo= 50ms Hi=300ms</small>				OFF						
Inhibit level Active Low				ON						
★ Inhibit level Active High				OFF						
★ Accept Can\$ 5					ON					
Reject Can\$ 5					OFF					
★ Accept Can\$ 10						ON				
Reject Can\$ 10						OFF				
★ Accept Can\$ 20							ON			
Reject Can\$ 20							OFF			
★ Accept Can\$ 50								ON		
Reject Can\$ 50								OFF		
★ Accept Can\$ 100									ON	
Reject Can\$ 100									OFF	

★ Manufacture setting

Note: (1)Please reset the bill acceptor after set the dip switch.

(2)Dip switches 1 to 5 are only used for pulse protocol.

DIP SWITCHES SETTING : 2

FUNCTION	SW1	SW2	SW3	SW4
★ Pulse Normal High	ON			
Pulse Normal Low	OFF			
★ Pulse Protocol		ON		
ICT Protocol		OFF		
Harness Disable			ON	
★ Harness Enable			OFF	
Ignore Sensor Problem(Note 1)				ON
★ Acknowledge Sensor Problem (Note 2)				OFF

★ Manufacture setting

Note : (1) Sensor 6 problem occurred ==>> BA will be still in working order.

(The face LED will be flashing in short green about 2 seconds everytime you restart BA.)

(2) BA will stop to work when it acknowledges Sensor 6 problem occurred.

(The face LED will be flashing in red.)

