

A6/V6 Option Switch Settings**Supported bill US\$ 1, 5, 10, 20 4 bills.**

A6/V6 dip-switch settings and functions:

FUNCTION	SW1	SW2	SW3	SW4	SW5	SW6	SW7	SW8	SW1	SW2	SW3	SW4
★ Reject US\$ 1	ON											
★ Accept US\$ 1	OFF											
★ Reject US\$ 5		ON										
★ Accept US\$ 5		OFF										
★ Reject US\$ 10			ON									
★ Accept US\$ 10			OFF									
★ Reject US\$ 20				ON								
★ Accept US\$ 20				OFF								
★ Reserved					ON							
★ Reserved					OFF							
★ High Acceptance						ON						
★ High Security						OFF						
★ Harness Disable							ON					
★ Harness Enable							OFF					
★ Inhibit Active High								ON				
★ Inhibit Active Low								OFF				
★ 1 pulse / one dollar									OFF	OFF		
2 pulse / one dollar									ON	OFF		
4 pulse / one dollar									OFF	ON		
20 pulse / one dollar									ON	ON		
★ Pulse Speed		50ms on / 50ms off									OFF	OFF
		60ms on / 300ms off									ON	OFF
		30ms on / 50ms off									OFF	ON
		150ms on / 150ms off									ON	ON

◆ Factory configuration has all switches in the OFF position.

Note : (1) Reset the bill acceptor after setting the dip switch.

(2) SW7 and SW8 of the 8-switch DIP and the 4-switch DIP are for pulse protocol only.

A6 Interface Settings: 2(Pulse/RS232)

	INTERFACE	SW1	SW2	SW3	SW4	
★	Credit-Pulse Normal HIGH	ON				
	Credit-Pulse Normal LOW	OFF				
★	Pulse Mode		ON			
	RS232 Interface		OFF			
★	Reserved			ON		
				OFF		
					ON	
					OFF	

★ Manufacture setting

	INTERFACE	SW1	SW2	SW3	SW4	
★	Reserved	ON				
		OFF				
★	Pulse Mode		ON			
★	RS232 Interface		OFF			
★	Reserved			ON		
				OFF		
					ON	
					OFF	

★ Manufacture setting

V6 Interface Settings: 2(M.D.B)

	INTERFACE	SW1	SW2	SW3	SW4	
★	Reserved	ON				
		OFF				
★	Reserved		ON			
★	M.D.B Interface		OFF			
★	Reserved			ON		
				OFF		
					ON	
					OFF	

★ Manufacture setting